

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/086285 A1

(51) International Patent Classification⁷: **H01Q 3/26**,
G01S 7/487, 13/90

(21) International Application Number:
PCT/EP2004/002569

(22) International Filing Date: 27 February 2004 (27.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **AGENCE
SPATIALE EUROPEENNE** [FR/FR]; 8-10, rue Mario
Nikis, F-75738 Paris Cedex 15 (FR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BAST, Daniel,
Christopher** [CA/CA]; Box 186, Sedley, Saskatchewan
S0G 4K0 (CA).

(74) Agents: **CABINET ORES** et al.; 36, rue de St Peters-
bourg, F-75008 Paris (FR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: PULSE-CODED REMOTE CALIBRATION OF AN ACTIVE PHASED ARRAY SYSTEM



(57) Abstract: A method for remotely calibrating an active phased array system, and more particularly an antenna, (APA), used in transmission and/or in reception, comprising transmitting and/or receiving a set of calibration pulses (RCP, TCP). Contrarily to methods known from the prior art, in which a reference signal is transmitted together with the calibration pulses in order to be able to perform a coherent detection of the calibration pulses at a remote station (GS), the method of the invention comprises incoherent demodulation of the calibration pulses and use of a signal processing procedure to account for the phase noise and amplitude fluctuations resulting from said incoherent demodulation. The method of the invention is particularly well suited for space applications, in which the active phased array system is an active phased array (APA) carried by a satellite (SAT) and the remote station (when it is present) is a ground station (GS).

WO 2005/086285 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.